

**Safety Data Sheet**  
**BROZINC**

**SECTION I - IDENTIFICATION**

**PRODUCT IDENTIFIER:** BROZINC  
**PRODUCT CODE:** 57000014-16AR  
**RECOMMENDED USE:** Galvanize Coating  
**RESTRICTIONS ON USE:** None known.  
**COMPANY NAME:** Brodi Specialty Products Ltd.  
**COMPANY ADDRESS:** 3175 14th Avenue, Unit 1, Markham, ON L3R 0H1  
**COMPANY PHONE:** 877-744-0751  
**EMERGENCY PHONE:** 800-255-3924

**SECTION II – HAZARDS IDENTIFICATION**

**CLASSIFICATION:** Aerosols Category 1  
Skin Irritant: Category 2  
Eye Irritant: Category 2A  
Carcinogenicity: Category 2  
Specific Target Organ Toxicity (Single Exposure): Category 3  
Specific Target Organ Toxicity (Repeated Exposure): Category 2  
Aspiration Hazard: Category 1

**HAZARD STATEMENT(S): DANGER:** Extremely flammable aerosol. Pressurized container: may burst if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

**PRECAUTIONARY STATEMENTS:** Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/ 122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors, or spray. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, and eye protection. **IF ON SKIN:** wash with plenty of water. **IF SKIN** irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **IF eye** irritation persists: Get medical advice/attention. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. Use only outdoors or in a well-ventilated area. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state, and national regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

**SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS**

<b>HAZARDOUS INGREDIENT</b>	<b>CAS NUMBER</b>	<b>PERCENT</b>
Heptane	142-82-5	10-30%
Propane/Butane	68476-86-8	10-30%
Acetone	67-64-1	7-13%
Xylene	1330-20-7	1-5%
Ethyl benzene	100-41-4	0.1-1%

**Trade Secret Information:** A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# Safety Data Sheet

## BROZINC

### SECTION IV - FIRST AID MEASURES

- EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if irritation persists.
- INGESTION:** Rinse mouth out with water. Do not induce vomiting unless directed by medical authority. Keep head below hips if vomiting occurs. Seek immediate medical attention. Aspiration hazard. Never give anything by mouth to an unconscious person.
- INHALATION:** Move to fresh air. If the person is breathing and has a pulse, do not start CPR. CPR is only for cardiac arrest (no pulse) or respiratory arrest (not breathing). For someone affected by aspiration, focus on airway management, oxygen, and keeping them comfortable while waiting for medical help. If the person is not breathing or has no pulse, CPR is appropriate, following standard guidelines. However, be aware that aspiration may have caused obstruction or chemical damage to the lungs. Rescue breaths should be performed carefully to avoid pushing more material into the lungs.
- SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Continue rinsing skin as needed. Seek medical attention if irritation persists.
- ACUTE HEALTH HAZARDS:** Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
- CHRONIC HEALTH HAZARDS:** Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.
- NOTE TO PHYSICIAN:** Treatment of overexposure should be directed at the control of symptoms and the clinical condition. Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

### SECTION V – FIRE-FIGHTING MEASURES

- EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, and foam.
- UNSUITABLE EXTINGUISHING MEDIA:** Water jets or streams which may spread flames.
- SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Shut off all sources of ignition. Use water spray to disperse vapor and cool fire exposed containers. Prevent run off from entering streams, sewers, or drinking water supply.
- UNUSUAL FIRE AND EXPLOSION HAZARDS:** EXTREMELY FLAMMABLE AEROSOL. Contents under pressure. Exposure to temperatures above 120 °F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Dense smoke, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and other oxides of carbon may be generated during a fire. Vapors heavier than air will settle in low lying areas and may travel to source of ignition and flash back. Vapors are heavier than air and can accumulate in low areas.
- HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, various hydrocarbons.

### SECTION VI – ACCIDENTAL RELEASE MEASURES

- PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.
- SPILL:** Eliminate all sources of ignition. Avoid contact with spilled material. Wear appropriate personal protective equipment. Clean up using rag or use some non-combustible material like vermiculite, sand or earth. Prevent spill from entering sewers, storm drains and natural waterways. Place waste in proper containers for disposal.
- WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.
- RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION VII – HANDLING AND STORAGE

- HANDLING AND STORAGE:** Do not use or store near heat, open flames or other sources of ignition. Wear proper personal protective equipment when using this product. Avoid contact with skin, eyes and clothing. Vapors may collect in low-lying areas. Use only with adequate ventilation. Do not inhale mist or vapor. Do not use or store with strong oxidizers. Store in a cool, dry area. Protect from sunlight. Store in a well ventilated area. Do not expose to temperatures exceeding 50 °C/122 °F. Do not pierce or burn, even after use. Wash hands thoroughly after handling.
- OTHER PRECAUTIONS:** Keep out of the reach of children. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not taste or swallow. Read and follow the directions on the product label. They are the best guide to using the product in the most effective manner. The label also gives you the necessary safety precautions to protect your health.
- INCOMPATIBILITY:** Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

### SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	500 ppm	400 ppm

# Safety Data Sheet

## BROZINC

Propane/n-Butane	Not Established	1000 ppm
Acetone	1000 ppm	250 ppm
Xylene	100 ppm	20 ppm
Ethyl benzene	100 ppm	20 ppm

**ENGINEERING CONTROLS / VENTILATION:** Use only outdoors or in a well-ventilated area. Material is heavier than air. Material may concentrate in low lying areas. Normal, forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally preferred.

**RESPIRATORY PROTECTION:** Use only in well-ventilated areas. If exposure levels are exceeded, then organic vapor cartridge respirator or SCBA will be needed.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses/goggles, chemical resistant gloves, and synthetic apron.

**ADDITIONAL MEASURES:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing spray. Do not touch eyes when using this product. Wash hands thoroughly with soap and water after use.

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Gray aerosol spray.

**ODOR:** Solvent.

**ODOR THRESHOLD:** N/D

**pH:** N/A

**MELTING POINT/FREEZING POINT:** N/D

**INITIAL BOILING POINT AND BOILING RANGE:** N/D

**FLASH POINT:** N/D

**EVAPORATION RATE:** > 3 Fast

**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**EXPLOSIVE LIMIT LOWER (%):** N/D

**EXPLOSIVE LIMIT UPPER (%):** N/D

**VAPOR PRESSURE (mm Hg):** N/D

**VAPOR DENSITY (AIR=1):** N/D

**RELATIVE DENSITY (H<sub>2</sub>O=1):** 1.16 - 1.30 @ 77 °F (25 °C).

**SOLUBILITY(IES):** Moderate.

**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D

**AUTOIGNITION TEMPERATURE:** N/D

**DECOMPOSITION TEMPERATURE:** N/D

**VISCOSITY:** N/D

### SECTION X – STABILITY AND REACTIVITY

**REACTIVITY:** If exposed to strong oxidizers, presents explosion hazard.

**CHEMICAL STABILITY:** Stable under normal storage conditions.

**POSSIBLE HAZARDOUS REACTIONS:** None known.

**CONDITIONS TO AVOID:** Temperatures greater than 122 °F and sources of ignition. Avoid incompatibles.

**INCOMPATIBLE MATERIALS:** Some plastics, strong oxidizing agents, acids, caustics, alkalis and chemically active metals.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon and other decomposition products.

### SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** Heptane (142-82-5): LD<sub>50</sub> (Oral, Rat) > 15000 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) > 3160 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 4h) 103 mg/L. Acetone (67-64-1): LD<sub>50</sub> (Oral, Rat) 5800 mg/kg; LD<sub>50</sub> (Oral, Mouse) 3000 mg/kg; LD<sub>50</sub> (Oral, Rabbit) 5340 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 8h) 50100 mg/m<sup>3</sup>; LC<sub>50</sub> (Inhalation, Mouse, 4h) 44,000 mg/m<sup>3</sup>. Xylenes (1330-20-7) LD<sub>50</sub> (Oral, Rat) 4000 mg/kg; LD<sub>50</sub> (Dermal, Rabbit, 24h) 12126 mg/kg; LC<sub>50</sub> (Inhalation, Vapor, Mice) 5000 ppm. Ethyl benzene (100-41-4) LD<sub>50</sub> (Oral, Rat) 3500 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) 15500 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 4h) 18 mg/L.

**ROUTES OF ENTRY:** Eyes, Inhalation, Skin

**EYES:** Causes serious irritation. May cause conjunctivitis with possible corneal injury.

**INGESTION:** Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting. Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia or edema.

**INHALATION:** May cause dizziness, nausea, central nervous system (CNS) effects.

# Safety Data Sheet

## BROZINC

**SKIN:** Causes irritation, redness, itching, and pain. Prolonged contact may cause defatting of the skin and dermatitis.

**MEDICAL CONDITION AGGRAVATED:** Pre-existing skin and respiratory disorders.

**ACUTE HEALTH HAZARDS:** Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

**CHRONIC HEALTH HAZARDS:** Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

**CARCINOGENICITY:** OSHA: No ACGIH: A3 - Animal Carcinogen NTP: No IARC: 2B - Possible OTHER: CA Prop 65

### SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Toxic to aquatic life with long lasting effects. **Acetone** (67-64-1): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 5540 mg/L; EC<sub>50</sub> (*Daphnia magna*, 48h) 6100 mg/L; EC<sub>50</sub> (*Selenastrum quadricauda*, 8d) 7500 mg/L; EC<sub>50</sub> (*Psuedomonas putida*, 16h) 1700 mg/L. **Heptane** (142-82-5): EC<sub>50</sub> (*Daphnia magna*, 48h) 1.50 mg/L. **Xylenes** (1330-20-7): LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h) 8 mg/L.

**PERSISTENCE AND DEGRADABILITY:** Component or components of this product are not biodegradable.

**BIOACCUMULATIVE POTENTIAL:** Component or components of this product are not expected to bioaccumulate.

**MOBILITY IN SOIL:** This product is mobile in soil.

**OTHER ADVERSE EFFECTS:** None known.

### SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of in accordance with local, state and federal regulations. Do not dump in sewers. Wrap container and place in trash collection. Do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

### SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

#### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, flammable.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

#### SHIPPING BY WATER:

##### VESSEL (IMO/IMDG)

**PROPER SHIPPING NAME:** Aerosols.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN1950

**PACKING GROUP:** N/A

**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant.

### SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Zinc (7440-66-6) Reportable Quantity = 1000 pounds. **Acetone** (67-64-1) Reportable Quantity = 5,000 pounds.

**SARA 311/312 HAZARD CATEGORIES:** Physical & health hazards.

**SARA 313 REPORTABLE INGREDIENTS:** **Xylenes** (1330-20-7). **Ethyl benzene** (100-41-4).

**CLEAN WATER ACT:** **Acetone** (67-64-1) is a hazardous substance.

**STATE REGULATIONS: California Proposition 65: WARNING:** This product can expose you to chemicals including **Ethylbenzene**, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). **Heptane** (142-82-5): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, IL, MA, NJ, PA, RI. **Acetone** (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA. **Xylene** (1330-20-7): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA DE, ID, ME, MA, MN, NJ, NY, PA, RI, WA. **Ethyl benzene** (100-41-4): Included on

# Safety Data Sheet

## BROZINC

State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states:  
CA, DE, ID, IL, ME, MA, MN, NJ, NY, PA, RI, WA, WI.

**INTERNATIONAL REGULATIONS:** No information available.

**VOLATILE ORGANIC COMPOUNDS (VOC):** 58.9%

**NFPA HEALTH:** 3

**NFPA FLAMMABILITY:** 3

**NFPA REACTIVITY:** 1

**NFPA OTHER:** None

**HMIS HEALTH:** \*3

**HMIS FLAMMABILITY:** 3

**HMIS REACTIVITY:** 1

**HMIS PROTECTION:** C

### SECTION XVI - OTHER INFORMATION

**PREPARATION BY:** William Bell

**DATE PREPARED:** 07/24/2013

**REVISION DATE:** 03/20/2026

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty expressed or inferred regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.