SAFETY DATA SHEET

1. Identification

Product identifier	Big Shot - Apple	
Other means of identification	1000017054	
Product code		
Recommended use	AIR FRESHENER	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Manufacturer		
Company name	Brodi Specialty Products	
Address	3175 – 14th Avenue	
	Unit #1	
	Markham, ON L3R 0H1	
	Canada	
Telephone	877-744-0751	
E-mail	Not available.	
Emergency phone number	Emergency - Outside US	1-952-852-4646
	Emergency - US	1-866-836-8855
Supplier	Not available.	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.
Response	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	68

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	15.18
Butane		106-97-8	14.82
Other components below	reportable levels		2

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

containers from fire area if you can do so without risk. Use water spray to cool unopened

Use standard firefighting procedures and consider the hazards of other involved materials. Move

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

containers. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol.

and precautions for firefighters

equipment/instructions

Specific methods

General fire hazards

6. Accidental release measures

Personal precautions, Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch protective equipment and damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate emergency procedures closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without Methods and materials for containment and cleaning up risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section

8. Exposure controls/personal protection

10 of the SDS).

US. ACGIH Threshold Limit Valu		Value
Components	Туре	value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Alberta OELs (Occupat	ional Health & Safety Code, Scl	nedule 1, Table 2)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3
		750 ppm
	TWA	1200 mg/m3
		500 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Canada. British Columbia OELs.	(Occupational Exposure Limit	s for Chemical Substances, Occupational Health and
Safety Regulation 296/97, as am		
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm
Canada. Manitoba OELs (Reg. 2 [.]	17/2006 The Workplace Safety	And Health Act)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Ontario OELs. (Control	of Exposure to Biological or C	hemical Agents)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	TWA	800 ppm
	of Lobor Degulation Despect	
Canada Quebec OFLs (Ministry		
		Value
Components	Туре	
Components		2380 mg/m3
Components	Type STEL	2380 mg/m3 1000 ppm
Components	Туре	2380 mg/m3 1000 ppm 1190 mg/m3
Components Acetone (CAS 67-64-1)	Type STEL TWA	2380 mg/m3 1000 ppm 1190 mg/m3 500 ppm
Canada. Quebec OELs. (Ministry Components Acetone (CAS 67-64-1) Butane (CAS 106-97-8)	Type STEL	2380 mg/m3 1000 ppm 1190 mg/m3

Components		Туре	Va	lue	
			10	00 ppm	
ological limit values					
ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, pl	ease see the source	document.			
ontrols dividual protection measur	or other engine exposure limits eyewash static	eering controls to mainta have not been establis m.	ain airborne leve hed, maintain ai	cess enclosures, local exha ls below recommended expo rborne levels to an acceptab	osure limits. If
Eye/face protection	Wear safety gl	asses with side shields	(or goggles).		
Skin protection					
Hand protection	Wear appropria supplier.	ate chemical resistant g	loves. Suitable g	loves can be recommended	by the glove
Other	Wear suitable	Wear suitable protective clothing.			
Respiratory protection	If permissible le air-supplied res		NIOSH mechar	nical filter / organic vapor car	tridge or an
Thermal hazards	Wear appropria	ate thermal protective c	lothing, when ne	cessary.	
eneral hygiene onsiderations	after handling		eating, drinking,	onal hygiene measures, such and/or smoking. Routinely	

9. Physical and chemical properties

Physical stateGas.FormAerosol.ColorNot available.OdorNot available.Odor thresholdNot available.pHNot available.Initial boiling point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedFlammability (solid, gas)Not available.Flammability limit - lower (%)2.4 % estimatedFlammability limit - lower (%)11.8 % estimatedFlammability limit - lower (%)Not available.Flammability limit - lower (%)Not available.Kaplosive limit - lower (%)Not available.KaplosiNot available.K	Appearance	
ColorNot available.OdorNot available.Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or exp:Imitial boiling (%)Flammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Kalative densityNot available.Kelative densityNot available.	Physical state	Gas.
OdorNot available.Odor thresholdNot available.PHNot available.Melting point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explored imit - lower (%)2.4 % estimatedFlammability limit - lower (%)11.8 % estimatedExplosive limit - lower (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.	Form	Aerosol.
Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or expire site limitsFlammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.	Color	Not available.
pHNot available.pHNot available.Melting point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or expive limitsImageFlammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.	Odor	Not available.
Melting point/freezing pointNot available.Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsImageFlammability limit - lower (%)2.4 % estimatedFlammability limit - lower (%)Not available.Flammability limit - lower (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Kalative densityNot available.Solubility(ies)Not available.	Odor threshold	Not available.
Initial boiling point and boiling range132.89 °F (56.05 °C) estimatedFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsFlammability limit - lower (%)Flammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%) (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor density Relative densityNot available.Solubility(ies)Not available.	рН	Not available.
rangeFlash point-156.0 °F (-104.4 °C) PROPELLANT estimatedEvaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsImage: Complex is the stimated of the	Melting point/freezing point	Not available.
Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsFlammability limit - lower2.4 % estimated(%)11.8 % estimatedFlammability limit - lower (%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Not available.	01 0	132.89 °F (56.05 °C) estimated
Flammability (solid, gas)Not available.Upper/lower flammability or explosive limitsFlammability limit - lower2.4 % estimated(%)11.8 % estimatedFlammability limit - upper11.8 % estimated(%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Not available.	Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Upper/lower flammability or explosive limitsFlammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Vapor bestimated	Evaporation rate	Not available.
Flammability limit - lower (%)2.4 % estimatedFlammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%) Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor density Relative densityNot available.Solubility(ies)Not available.	Flammability (solid, gas)	Not available.
(%)Flammability limit - upper (%)11.8 % estimatedExplosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)	Upper/lower flammability or exp	losive limits
(%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Vapor density	-	2.4 % estimated
Explosive limit - upper (%)Not available.Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Vation (Content of the content of	• • • •	11.8 % estimated
Vapor pressure60 - 70 psig @70F estimatedVapor densityNot available.Relative densityNot available.Solubility(ies)Vative density	Explosive limit - lower (%)	Not available.
Vapor densityNot available.Relative densityNot available.Solubility(ies)	Explosive limit - upper (%)	Not available.
Relative density Not available. Solubility(ies)	Vapor pressure	60 - 70 psig @70F estimated
Solubility(ies)	Vapor density	Not available.
	Relative density	Not available.
Solubility (water) Not available.	Solubility(ies)	
	Solubility (water)	Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.18 g/cm3 estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.784 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

Rat Mouse Rat		1355 mg/l 1237 mg/l, 120 Minutes
		1237 ma/l 120 Minutes
		1237 ma/L 120 Minutes
		1237 mg/L 120 Minutes
		1237 ma/L 120 Minutes
Rat		1207 mg/l, 120 mmatos
Rat		52 %, 120 Minutes
		1355 mg/l
		658 mg/l/4h
e based on addi	onal component data not shown.	
Prolonged ski	contact may cause temporary irritation	n.
Causes seriou	s eye irritation.	
า		
Not a respirate	ry sensitizer.	
This product is	not expected to cause skin sensitizati	ion.
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
arcinogenicity	A4 Not classifiable as	s a human carcinogen.
)	Not classifiable as a	human carcinogen.
This product is	not expected to cause reproductive o	r developmental effects.
May cause dro	wsiness and dizziness.	
Not classified.		
Not likely, due	to the form of the product.	
I		
The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environmer		
	Species	Test Results
5050		
		21.6 - 23.9 mg/l, 48 hours
LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
e based on addi	onal component data not shown.	
No data is ava	lable on the degradability of this prod	uct.
ctanol / water (÷ ·	
	-0.24	
No data availa		
		depletion photochemical ozone creation
	Prolonged skin Causes serious Not a respirato This product is No data availat mutagenic or g arcinogenicity) This product is May cause dro Not classified. Not likely, due The product is possibility that EC50 LC50 e based on additi No data is avai ctanol / water (lo	Prolonged skin contact may cause temporary irritation Causes serious eye irritation. Not a respiratory sensitizer. This product is not expected to cause skin sensitization No data available to indicate product or any component mutagenic or genotoxic. A4 Not classifiable as a This product is not expected to cause reproductive of May cause drowsiness and dizziness. Not classified. Not classified. Not likely, due to the form of the product. The product is not classified as environmentally haza possibility that large or frequent spills can have a har Species EC50 Water flea (Daphnia magna) LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss) e based on additional component data not shown. No data is available on the degradability of this prod ctanol / water (log Kow)

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

56	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
This product meets the exemption	tion requirements and may be shipped as a limited quantity.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations		
Controlled Drugs and Subst	ances Act	
Not regulated.		
Export Control List (CEPA 1	999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.		
Precursor Control Regulatio	ns	
Acetone (CAS 67-64-1)	Class B	
International regulations		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable.		
Kyoto protocol		
Not applicable. Montreal Protocol		
Not applicable. Basel Convention		
Not applicable.		
International Inventories		
	Inventory name	On inventory (vec/ne)*
Country(s) or region Australia	Inventory name Australian Inventory of Chemical Substances (AICS)	On inventory (yes/no)* No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Vee" indicates that all seven ar		

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	05-11-2017
Revision date	05-11-2019
Version #	02

We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.